

**Bobcat®***One Tough Animal.*

PA450vP PORTABLE AIR COMPRESSOR

SPECIFICATIONS

| | PA450vP |
|-----------------------------------------------|----------------------------------------------|
| COMPRESSOR ROTARY SCREW / SINGLE STAGE | |
| Free-Air Delivery (low/high) | 450/400 cfm (12.7/11.3 m ³ /min.) |
| Rated Operating Pressure (low/high) | 150/200 psig (10.3/13.8 bar) |
| Pressure Range | 80–225 psig (5.5–15.5 bar) |
| Air Discharge Outlet NPT Size | 1.25 in. (31.8 mm) |
| Air Discharge Outlet Quantity | 1 |
| Fuel Tank Capacity | 60 gal. (227 L) |
| ENGINE | |
| Make & Model | Cummins F3.8L |
| Emissions Tier Level | Tier 4 Final (T4F) |
| Number of Cylinders | 4 |
| Displacement | 231 cu. in. (3.8 L) |
| Rated Speed (low/high) | 2500/2250 rpm |
| Idle Speed | 1500 rpm |
| Bhp @ Rated Speed (low/high) | 173/172 Bhp (129/128 kW) |
| Electrical | 24V |
| Hours of Operation @ Full Load (low/high) | 8 hr. |
| DIMENSIONS WITH RUNNING GEAR | |
| Length | 154.2 in. (3917 mm) |
| Width | 78.2 in. (1986 mm) |
| Height | 73.3 in. (1862 mm) |
| Track Width | 66.6 in. (1692 mm) |
| Tire Size | 15.0 in. (381 mm) |
| Shipping Weight (without fuel) | 4334 lb. (1966 kg) |
| Working Weight (with fuel) | 4776 lb. (2166 kg) |
| DIMENSIONS WITHOUT RUNNING GEAR | |
| Length | 107.0 in. (2718 mm) |
| Width | 60.7 in. (1542 mm) |
| Height | 61.0 in. (1549 mm) |
| Shipping Weight (without fuel) | 4071 lb. (1846 kg) |
| Working Weight (with fuel) | 4513 lb. (2047 kg) |

KEY FEATURES

The Bobcat® PA450vP dual pressure portable air compressor delivers versatile air power in a compact, easy-to-maneuver footprint.

- Experience versatile performance with programmable HI/LO pressure options, providing customizable solutions to perfectly suit your needs.
- The PA450vP delivers an airflow ranging from 400 to 450 cfm at pressures between 150 to 200 psi.
- This compressor's compact design features large access doors for hassle-free maintenance.
- Ideal for construction, abrasive blasting, and fiber optic cable installation, this air compressor excels in a variety of applications.



Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

The images shown are for illustration purposes only and may not be an exact representation of the product.

DOOSAN

Bobcat Company is a member of the Doosan Group. Doosan is a global leader in construction, grounds maintenance and material handling equipment, power and water solutions, and engineering that has proudly served customers and communities for more than a century. Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries.

www.bobcat.com

©2024 Doosan Bobcat North America. All rights reserved.

